



## Tallicin® 2500

### LUBRICANT BASE STOCK

#### TYPICAL CHARACTERISTICS

Appearance	Clear Amber Fluid
Odor	Fatty
Lb/gal @ 60°F	8.3 - 8.5
Solubility in Water	Complete
Solubility in 100 Vis Naphthenic Oil	Dispersible*
Solubility in 100 Vis Paraffinic Oil	Dispersible*
Solubility in Esters	Dispersible*
Falex Break Point(@ 5%concentration)	2500-3500 lb.

\* Can be coupled in with additives

#### APPLICATION

Tallicin ®2500 is completely water soluble. Tallicin ®2500 obtains excellent boundary lubrication results. Tallicin ®2500 can be used on most ferrous and non-ferrous metals. Incorporation of appropriate corrosion inhibitors based on the metal being worked will be necessary. Complete biodegradability makes this an environmentally friendly product.

#### PROUDCT USES (For professional use only. Not intended for retail sales.)

2 - 10%

#### CONTAINER SIZES

5 Gallon Pail and 55 Gallon Drum

The information contained herein is to the best of our knowledge true and accurate and any suggestions are made without guarantee, express or implied, since the conditions of use are beyond our control. Pflaumer Brothers, Inc. disclaims any liability incurred in connection with the use of these data or suggestions.