



## Tallicin® 4550

Imparts Improved Flow and Leveling in High Solids Coatings

OPTICAL CLARIFIER/BRIGHTENER FOR WATER-BASED SYSTEMS

### TYPICAL CHARACTERISTICS

Appearance	Clear Liquid
Weight per Gallon, Lbs	8.4 @ 25°C.
Flash Point (TCC)	None

### COMPATIBILITY

Tallicin® 4550 is used in water-based clear coatings.

### APPLICATIONS

Tallicin® 4550 is designed to clarify or brighten clear coatings applied over natural surfaces such as wood, concrete, sandstone and white or light colored surfaces. It can be used to take the yellowness out of coatings and can be used as a fluorescent whitener. When used over dark surfaces such as black or dark blue, optically brightened finishes may have a bluing effect.

### FEATURES

Brightens and clarifies clear coatings.

### PROUDCT USES (For professional use only. Not intended for retail sales.)

Typical use levels range from 0.25-0.5% by weight based on finished formula.

### CONTAINER SIZES

5 Gallon Pails and 55 Gallon Drums.

The information contained herein is to the best of our knowledge true and accurate and any suggestions are made without guarantee, express or implied, since the conditions of use are beyond our control. Pflaumer Brothers, Inc. disclaims any liability incurred in connection with the use of these data or suggestions.