



Tallicin® 4100

ANTIFOAM AND DEFOAMER FOR SOLVENT BASED SYSTEMS

TYPICAL CHARACTERISTICS

Appearance	Colorless Liquid
Weight Per Gallon, Lbs	6.6 ±0.1
Flash Point (TCC)	40°C

COMPATIBILITY

Tallicin® 4100 is an anti-foam/defoamer that is compatible in a wide range of solvent-based coatings.

APPLICATIONS

Tallicin® 4100 is an anti-foam/defoamer for solvent based systems that are susceptible to foaming from high-shear conditions during processing or application. Example of such high-shear conditions include flow-coating and airless spray applications where foaming may be induced and in paint-filling operations where effective anti-foaming may be required.

FEATURES

Prevents the formation of foam from high-shear conditions.

PROUDUCT USES (For professional use only. Not intended for retail sales.)

Tallicin® 4100 is recommended for use in the range of 0.3% to 1.0% based on total formulation weight. Always use the least amount necessary to produce the desired effect.

CONTAINER SIZES

5 Gallon Pails and 55 Gallon Drums.

The information contained herein is to the best of our knowledge true and accurate and any suggestions are made without guarantee, express or implied, since the conditions of use are beyond our control. Pflaumer Brothers, Inc. disclaims any liability incurred in connection with the use of these data or suggestions.