



Tallicin® WETTING AGENT 3405

WETTING AGENT/ DISPERSANT WITH E.P./ A.W. PROPERTIES

TYPICAL CHARACTERISTICS

Appearance	Dark Brown Liquid
Odor	Citrus
Lb/gal @ 60°F	8.05 - 8.35
Flash Point (TCC)	250°C
Acid #	73±5
Pour Point	+ 20°C
Solubility in 100 Vis Naphthenic Oil	Soluble
Solubility in 100 Vis Paraffinic Oil	Soluble
Solubility in Esters	Soluble
4 Ball Antiwear (@ 5% Concentration in White Mineral Oil)	0.45mm Scar* * ASTM D-4172 (Modified): 1200RPM, 40Kg Load, 61°C, 1 Hour

APPLICATION

Tallicin® Wetting Agent 3405 is soluble in both naphthenic and paraffinic oils as well as esters. Tallicin® Wetting Agent 3405 is an extreme pressure/antiwear additive. It was designed for use in lubricant applications that are required to have high performance demands. Tallicin® Wetting Agent 3405 has superior clinging ability and can be used in gear oils. Tallicin® Wetting Agent 3405 is also effective in dispersing Molybdenum Disulfide and Teflon used in lubricant formulations.

PROUDCT USES (For professional use only. Not intended for retail sales.)

0.5% - 10.0% by wt.

CONTAINER SIZES

5 Gallon Pails and 55 Gallon Drums
(03 Kg)

The information contained herein is to the best of our knowledge true and accurate and any suggestions are made without guarantee, express or implied, since the conditions of use are beyond our control. Pflaumer Brothers, Inc. disclaims any liability incurred in connection with the use of these data or suggestions.